



Interactive  
Comment

## ***Interactive comment on “Site effect classification based on microtremor data analysis using concentration–area fractal model” by A. Adib et al.***

**A. Adib et al.**

geo.adib@yahoo.com

Received and published: 18 October 2014

Attached is the final version of the edited article will be sent

Interactive comment on Nonlin. Processes Geophys. Discuss., 1, 1133, 2014.

Full Screen / Esc

Printer-friendly Version

Interactive Discussion

Discussion Paper



1 Site effect classification based on microtremor data analysis using  
2 Concentration-area fractal model

3 Ahmad Adibi<sup>1\*</sup>, Peyman Afzal<sup>1,2</sup>, Kobra Heydarzadeh<sup>3</sup>

4 1-Department of Mining Engineering, South Tehran Branch, Islamic Azad University, Tehran, Iran

5 Email: geo.adib@yahoo.com & adib@azad.ac.ir

6 2-Camborne School of Mines, University of Exeter, Penryn, UK

7 Email: peymanafzal@yahoo.com

8 3-Zamin Kav Environmental & Geology Research Center, Tehran, Iran

9 Email: k.heydarzadeh@yahoo.com

10  
11 **Abstract**

12 The aim of this study is to classify the site effect using concentration-area (C-A) fractal model in  
13 Meybod City, Central Iran, based on microtremor data analysis. Log-log plots of the frequency,  
14 amplification and vulnerability index (k-g) indicate a multifractal nature for the parameters in the area.  
15 The results obtained from the C-A fractal modeling reveal that proper soil types are located around the  
16 central city. The results derived via the fractal modeling were utilized to improve the Nogoshi's  
17 classification results in the Meybod city. The resulted categories are: (1) hard soil and weak rock with  
18 frequency of 6.2 to 8 Hz, (2) stiff soil with frequency of about 4.9 to 6.2 Hz, (3) moderately soft soil with  
19 the frequency of 2.4 to 4.9 Hz, and (4) soft soil with the frequency lower than 2.4 Hz.

20 **Keywords:** Site effect classification, Concentration-area fractal model, Microtremor, Frequency.

21 Meybod city, Iran

22 **1. Introduction**

23 Site effect caused by an earthquake may vary significantly in a short distance. Seismic waves  
24 trapping phenomenon leads to amplify vibrations amplitudes that may increase hazards in sites with soft  
25 soil or topographic undulations. Theoretical analysis and observational data have illustrated that each site  
26 has a specific resonance frequency at which ground motion gets amplified (Bard, 2000; Mukhopadhyay  
27 and Bormann, 2004).

28 Microtremor data analysis is applied in the recognition of the soil layers, prediction of shear-wave  
29 velocity of the ground, and evaluation of the predominant period of the soil during earthquake events. It

\* Corresponding author Email: [Adib@azad.ac.ir](mailto:Adib@azad.ac.ir)

[Full Screen / Esc](#)[Printer-friendly Version](#)[Interactive Discussion](#)[Discussion Paper](#)

**Fig. 1.** Site effect classification based on microtremor data analysis using Concentration-area fractal model

