Reply to Reviewer 1

We thank the reviewer for his general support of our work. We also greatly appreciate the time and the effort invested by him in providing a meaningful review. We have adopted some of the reviewer's suggestions and corrected the errors and misprints noticed by him. Since there are, however, some points of disagreement between us, we welcome his suggestion to debate the differences. In the following we provide the detailed replies to the reviewer's comments. The reviewers' comments are in *italics*.

1. The restrictive role of periodic conditions in the numerical simulations is drastically overestimated.

It seems to be an axiom that if waves are well localized in the domain of consideration, then the boundary conditions do not matter (whether they are periodic as in the numerical tank, reflective as in a laboratory, etc).

This seems to be the major point of disagreement. As it is our desire to address the reviewer's inputs, we would appreciate greater clarification as to what is meant by the statement "It seems to be an axiom that if waves are well localized in the domain of consideration, then the boundary conditions do not matter (whether they are periodic as in the numerical tank, reflective as in a laboratory, etc)." We are unaware of any axiom which categorically states the boundary conditions do not matter.

Moreover, it is generally known (including from personal experience) that reflections from the far end of the wave flume can change the wave pattern in the whole tank significantly. This is the reason why the wave energy absorbing beach is installed in all wave flumes (including ours), and active control of the wave maker is applied as well to remove secondary reflections in some tanks. In all our experiments, great care is taken to study the spatial evolution of wave trains of finite duration and we limit the measurements to locations that are sufficiently far from the end of the tank to mitigate the effects of secondary reflection, however minor they may be.

As for numerical tanks, a similar approach may be adopted. Note that in recent years, numerous numerical wave tanks were based on various versions of the Boundary Elements Method and adopted by a number of research groups. The main motivation for those is to remove the requirement of periodic boundary conditions. One of the earliest attempts in this direction that we are aware of is the paper by Grilli et al. (Engng. Analysis with Boundary Elements 6 (2), 97-107, 1989). At the start of Section 2.5 in that paper it reads: "In the present paper, the Laplace equation is solved in the physical space, since we intend to generate non-periodic waves and to absorb them. The presentation is limited in a 2-D model, but can in principle be extended to 3-D problems".

Moreover, regarding all experimental studies reporting on nonlinear unidirectional propagating wave trains published since the late 1970s, beginning from seminal papers by Yuen and Lake, we are unaware of any results indicating that spatially periodic boundary conditions can indeed be observed in experiments.

"When there is a mean current, the surface potential is not localized."

We wish to stress that the application of the method proposed by Chalikov and Sheinin (2005) or

any other method of conformal mapping does provide the velocity potential (not just the surface elevation) in the whole domain of calculation. The Stokes drift current has a vertical velocity profile and it is basically concentrated in a thin upper layer only. The necessity for mass conservation in the experimental wave tank (closed at both ends) results in a slow backward current in the lower layers that practically does not affect waves under deep water conditions. This was also observed in our experimental facility. It is therefore impossible to apply the Galilean transformation (as suggested by the reviewer) to mitigate the effect of the Stokes' drift current.

"The numerical simulations presented in the paper are inaccurate ... due to the rough initial condition (since the bound waves are completely disregarded),"

The bound waves are in fact accounted for in our simulations. We appreciate the suggestion by the reviewer to use Dysthe equations to calculate the initial condition. However, a different method was used in our paper. Prior to integration in time, the linear Peregrine Breather solution was modified to satisfy the governing equations; the initial conditions thus effectively include the bound waves as well and were obtained by applying an iterative procedure as described in Chalikov and Sheinin (2005). Also, our computational domain was longer than the effective length of the wave train.

2. The bibliographic review is lopsided.

The Peregrine breather and many other analytic solutions have been reproduced in laboratory experiments many times by A. Chabchoub with colleagues [Chabchoub, A., Hoffmann, N., Akhmediev, N. Rogue wave observation in a water wave tank. Phys. Rev. Lett. 106, 204502, 2011 and subsequent papers].

Shemer and Alperovich (2013) [hereafter referred to as SA] demonstrated that there were essential deficiencies in the original paper by Chabchoub et al. (2011). The spectra presented in JGR (2013) do not contain any quantitative data and hardly qualitative information as well, in a sharp contrast to SA. In private discussions with Amin Chabchoub, no evidence was presented by him to counter the points highlighted in SA. For these reasons, these two papers were not cited in our study.

As for the paper by Slunyaev et al (2013), it will be cited in the revision of our manuscript although we wish to point out that many of the experimental and numerical results featured in that paper were already published in SA, half a year earlier.

3. The interpretation of analytic solution (6) is wrong.

In principle, we agree with the reviewer's comment and will replace the term "asymmetric in space" to "aperiodic in space" to stress the point that the analytical solution of the Peregrine Breather evolving along the tank lacks spatial periodicity.

4. The discussion of wave kinematics in page 1175-1176 is questionable. ... one may assume quite the opposite – that the laboratory measurements were probably not accurately enough to claim the correctness of the breaking criterion.

We believe that the comment is biased for the following reasons. In both Shemer and Liberzon (2014) and in the present manuscript, state of the art experimental methods were applied and we are curious as to what led the reviewer to question the accuracy of our results and the validity of conclusions. While it seems that the experimental findings by Chabchoub in PRL 2011 and later papers regarding the observability of breathers are accepted unconditionally and presented as truth, the reviewer questions the accuracy of our results without any substantiation.

We would like to stress that the validity of the suggested breaking criteria was demonstrated in two independent studies with different experimental methods used. In Shemer and Liberzon, accurate Particle Tracking Velocimetry (PTV) measurements of Lagrangian velocity and acceleration were performed (ref. to Figures 4, 7, and 9 for velocity and Figure 10 for acceleration). The crest velocities at the inception of breaking were measured using digital video image processing. Moreover, the steepest crest propagation velocities proved to be in very good agreement with analytical solutions based on the Peregrine Breather. In that paper, the video clips were also presented as a supplement, providing visual evidence of strong acceleration of fluid particles at the inception of breaking. In the present study, the focus was made on detailed comparisons of fully nonlinear solutions in space with the time histories of the surface elevation measured at numerous locations along the tank. The instantaneous steepest crest velocities were obtained from data acquired by closely located probes. We do not see any reason to question the accuracy of our experimental results especially since the same level of scrutiny is not applied to other experiments. The possible reasons for minor discrepancies between experimental and numerical results are candidly discussed in the manuscript.

5. Remarks to section 'Discussion and conclusions'.

In the present manuscript, we do not generate the boundary condition at the wavemaker. We just discuss the method to generate the appropriate initial wavemaker driving signal. As such, the reference suggested by the reviewer does not seem to be directly relevant.

We see this Section as an integral part of the paper where the total body of results presented before are discussed from a common view point and without unnecessary repetitions.

The truncation of an infinite wave train is indeed a common approach and was applied effectively in all studies of wave group propagation. We wish to clarify that we do not claim any element of novelty here and simply aim to provide a detailed description of the experimental accuracy. Shemer et al. have applied a similar approach since the late 1980s, as have many others.

The Dysthe equation was indeed not discussed in this paper. An appropriate reference to SA will be given here in the revision.

6. It is not clear, was the breaking observed in the numerical simulations or not, how the accuracy of numerical simulations was controlled.

The accuracy of numerical simulations was tested using the standard procedure of reducing the

integration steps, as specified in the manuscript.

We thank the reviewer for highlighting the apparent inconsistency regarding the late stages of the evolution. In our simulations the horizontal fluid velocity appears to be discontinuous at a t/T_0 approximately 62. This also seems to fit with what is shown in Fig. 9 as the max crest height exceeds 3. We recall that these 2 plots are for the numerical simulations only of the temporal evolutions of spatially distributed functions.

We clarify that this does not necessarily mean that the computation has to break down at $t/T_0 \approx 62$. The numerical computation breaks down when it just blows up. One of the goals of the paper is to determine up to what time do we want to set the applicability of the simulation results. Beyond that time, we say that the result is not useful. So since the simulation of the surface elevation ran till around $74T_0$, we used the data up to that time. However, as can be seen in Fig. 4 (surface elevations variation with time for fixed x values), using the data up to t/T0 = 62 does not affect the results shown in Fig. 10 - which aims to directly compare between experiments and the relevant post-processed results from the simulations.

Less significant remarks:

7.1. Abstract - We will change the phrase "A method was developed..." to "A method was applied..."

7.1. - We accept the remark and the manuscript will be modified to include intermediate depth.

7.2. - We question the observation since significant spectral broadening associated with the focusing of the Peregrine Breather seems to be irreversible.

7.3. – We accept the comment and will change the first sentence to "Shemer and Alperovich (2013) demonstrated that the modified nonlinear Schrödinger (MNLS, or Dysthe) equation was advantageous in describing the PB evolution along a laboratory tank as compared to the NLS equation (Dysthe, 1979)."

7.4. – The sentence will be changed "Shemer and Liberzon (2014) noticed that the spectral widening, being an essentially nonlinear process, occurs at slow spatial and temporal scales. Hence, it was found that the wave train behavior with background steepness of about 0.1 is still described by the PB solution of the NLS equation with reasonable accuracy, as long as the surface elevation spectrum remains sufficiently narrow and the maximum wave height in the train remained below approximately twice that of the background."

7.5. – The notation is correct. On page 1164, we refer to physical variables whereas on page 1168, the axes are defined according the conformal mapped space.

7.6. – We accept the comment, the typo will be corrected.

7.7. – We accept the comment and the year will be revised accordingly.

7.8. – We accept the comment and the figure will be corrected.

Reply to Reviewer 2

We thank the reviewer for his general support of our work and greatly appreciate the time and effort invested by him in providing a meaningful review.

We have accepted the reviewer's suggestions and wish to clarify certain points raised by him. In the following we provide the detailed replies to the reviewer's comments. The reviewers' comments are in italics.

1. First, it is noted that the authors' focus is limited to the special class known as the 2D Peregrine breather wave packets.

Given that the actual initial condition for the simulations and the initial driving signal for the wavemaker have been modified and are fundamentally different from the PB, the results on steep crests in the wave train presented in this study are of generic nature and applicable beyond the 2D Peregrine breather wave packets. The crest slowdown was also observed in some other studies, as noticed by the reviewer. This fact is now accounted for in the revision. To stress that point, last line of the 4th paragraph of Section 5 was modified.

2. The wording on p.1179, lines 7-10 of the present paper should probably be modified to better reflect the generality and nature of this important advance in knowledge of water wave kinematics.

We accept the reviewer's comments; they are now accounted for in the revision.

3. From a careful reading of this discussion and inspection of the key figures 9 and 10, it becomes evident that various sources operative lead to residual uncertainties in their companion model and observational assessment. These uncertainties preclude the conclusive evidence required for certainty of its validity. Hence I am obliged to recommend that the authors accordingly modify their wording on lines 19-21 of p.1179 of the paper.

We accept the reviewer's suggestion to some extent and have changed the statement to a somewhat vaguer formulation. On the other hand, the reviewer's comment prompted us to point out that our conclusions are also supported by visual evidence as seen in video clips presented in the Supplements to both the present manuscript and to Shemer and Liberzon.

New results on this topic that reduce these uncertainties have recently been published for a wider range of cases [Saket et al., ArXiv 1508.07702; Barthelemy et al., ArXiv 1508.06002]. These results provide evidence that questions the validity of the kinematic breaking condition as the primary determinant of breaking onset.

It is our understanding that these two manuscripts were uploaded at the end of August. We should point out that the present paper was motivated to a large extent by an earlier study by Shemer and Liberzon (PoF 2014). The present manuscript was submitted on July 1 and made available online on July 24, 2015. We therefore do not feel that it is appropriate to cite manuscripts submitted after our work already was published in NPGD.

Manuscript prepared for Nonlin. Processes Geophys. with version 2015/04/24 7.83 Copernicus papers of the LATEX class copernicus.cls. Date: 21 September 2015

Steep Unidirectional Wave Groups - Fully Nonlinear Simulations vs Experiments

Lev Shemer¹ and Bernard K. Ee¹

¹School of Mechanical Engineering, Tel Aviv University, Tel Aviv 69978, Israel *Correspondence to:* Lev Shemer (shemer@eng.tau.ac.il)

Abstract. A method was <u>developed applied</u> to carry out detailed <u>qualitative quantitative</u> comparison of fully nonlinear computations with the measurements of unidirectional wave groups. Computational results on evolving wave groups were compared with <u>the previous</u> available experiments. The local surface elevation variation, evolution of envelope shapes, the velocity of propagation of

5 the steepest crests in the group and their relation to the height of the crests were obtained numerically and experimentally. Conditions corresponding to incipient wave breaking were investigated in greater detail. The results shed additional light on the limits of applicability of the computational resultsmechanisms leading to the breaking of steep waves, as well as on mechanisms leading to the breaking of steep waves, as well as on mechanisms leading to the breaking of steep waves.

10 1 Introduction

Over the past few decades, rogue, or freak, waves have attracted considerable interest due to their destructive impact on offshore structures and ships (Dysthe et al., 2008; Kharif et al., 2009). A number of possible mechanisms for rogue wave generation have been explored. Wave-current and wavebathymetry interactions may result in appearance of rogue waves (Kharif et al., 2009). Extremely

- 15 steep waves in ocean are thus usually affected by the directional characteristics of the wave field. Nevertheless, considerable effort has been invested in recent decades to study unidirectional wave fields. The accumulated results clearly demonstrate that investigation of both deterministic and random unidirectional waves can lead to a better understanding of mechanisms leading to appearance of rogue waves in the presence of directional spreading as well. Experimental studies of 2-D wave
- 20 fields in wave basins require large and expensive facilities and are subject to numerous limitations on the wave parameters. Generation of unidirectional wave groups in long tanks by a computercontrolled wavemaker offers significant advantages in terms of availability and versatility of operational conditions. Extremely steep waves can be generated due to constructive interference of numerous harmonics. While this focusing mechanism is basically linear, it is strongly affected by
- 25 nonlinearity (Shemer et al., 2007; Bateman et al., 2012). An alternative, essentially nonlinear, mechanism is related to the specific properties of the governing equations. To that end, the nonlinear

Schrödinger (NLS) equation (Zakharov, 1968; Hasimoto and Ono, 1972), applicable for description of diverse nonlinear physical phenomena, is the simplest theoretical model describing evolution of narrow-banded wave groups in deep and intermediate depth water. This equation attracts special

- 30 interest in rogue waves studies since it admits analytical solutions such as the so-called Kuznetsov– Ma breathing solitons (Ma, 1979; Kuznetsov, 1977) (Kuznetsov, 1977; Ma, 1979). These solutions of the NLS equation present spatially localized patterns that oscillate in time. The closely related Akhmediev breather (Akhmediev et al., 1987) is periodic in space. When the periodicity in time and space tends to infinity, both these types of solution tend to a simple Peregrine Breather (PB)
- 35 (Peregrine, 1983). It is localized in time and space, breathes only once and attains a maximum crest height that exceeds that of the background wave train by a factor of three. For this reason, the Peregrine and other breather-type solutions of the NLS equation have been proposed as rogue wave prototypes (Dysthe and Trulsen, 1999; Osborne et al., 2000; Shrira and Geogjaev, 2010) (Dysthe and Trulsen, 1999; Osborne et al., 2000; Shemer and Alperovich (2013) conducted a series of experiments on the evolution of the Peregrine
- 40 breather (PB) along a wave tank. They demonstrated that the experimental results diverge from the Peregrine's solution of the NLS equation. Notable asymmetry of the crest was observed, in agreement with many earlier studies of extremely steep waves (Babanin et al., 2007). The discrepancy between the fully symmetric NLS solution and experiments manifests itself mainly in significant asymmetric widening of the wave spectrum, as well as in notably slower than predicted by the PB
- 45 solution amplification of the wave height. Moreover, these experiments suggested that, contrary to the behavior of the PB, there would be no return to the initial nearly monochromatic wave train. Similar conclusions based on fully nonlinear simulations of PB evolution in time were reached by Slunyaev and Shrira (2013). Shemer and Alperovich (2013) demonstrated that the modified nonlinear Schrödinger (MNLS, or Dysthe) ((Dysthe, 1979)) equation was advantageous in describing the
- 50 PB evolution <u>along the laboratory tank</u> as compared to the NLS equation(Dysthe, 1979). The improved performance of the Dysthe model was attributed in Shemer and Alperovich (2013) to the additional 4th order terms in this equation that account for the finite spectral width (Kit and Shemer, 2002).

Shemer and Liberzon (2014) noticed took advantage of the fact that the spectral widening, being an essentially nonlinear process, occurs at slow spatial and temporal scales. Hence, it was found that the wave train behavior with background steepness of about 0.1 is still described by the PB solution of the NLS equation with reasonable accuracy, as long as the surface elevation spectrum remains sufficiently narrow and the maximum wave height in the train remained below approximately twice that of the background. This observation enabled Shemer and Liberzon (2014) to take advantage

60 of utilize the available PB analytic solution to design experiments with PB in which the height of the steepest wave in the train at a prescribed measuring location can be controlled, thus facilitating quantitative studies of the incipient wave breaking. Their study was motivated by an earlier attempt by Shemer (2013) to examine the kinematics of the steep wave on the verge of breaking using the Zakharov equation (Zakharov, 1968). By comparing the computational results with experimental

- observations reported in Shemer et al. (2007), the conclusion was reached that wave breaking may occur when the horizontal liquid velocity at the crest becomes sufficiently high (Shemer, 2013). These computations also showed that the maximum negative vertical Lagrangian acceleration seems to remain significantly below the acceleration of gravity g, so that the Phillips dynamic breaking criterion cannot be satisfied (Phillips, 1958). Computations of steep wave kinematics accurate up
- 70 to the 3rd order in the wave steepness demonstrated, though, that this approximation, while largely adequate for determination of the shape of the surface elevation, was insufficient for the accurate characterization of the kinematics of steep waves (Shemer, 2013). In order to overcome this limitation, the kinematic parameters of the steepest wave in the PB-PB-like wave train were determined experimentally in Shemer and Liberzon (2014) simultaneously with estimates of the propagation
- 75 velocity of the steepest crest. To this end, two synchronized video cameras were used to image the wave field. The maximum possible horizontal Lagrangian velocities and accelerations at the surface of steep water waves were measured by Particle Tracking Velocimetry (PTV) for gradually increasing crest heights, up to the inception of a spilling breaker. Actual crest and phase velocities were estimated from video recorded sequences of the instantaneous wave shape as well as from surface
- 80 elevation measurements by wave gauges. The slow-down of the crest as it growths steeper was observed. It was suggested in Shemer and Liberzon (2014) that the inception of a spilling breaker is associated with the horizontal velocity of water particles at the crest attaining that of the crest, thus confirming the kinematic criterion for the inception of breaking.
- In the present study, we aim to extend the numerical analysis of the conditions prevailing at the inception of breaking of the steepest crest in the PB-PB-like wave train by carrying out fully nonlinear simulations. The simulation were performed using conformal mapping method approach developed by Chalikov and Sheinin (1998, 2005) (hereafter known-referred to as the CS model). A somewhat different implementation of this approach was suggested by Milewski et al. (2010). Recently, Perić et al. (2014) reported on direct numerical simulations based on the volume of fluid
- 90 method to solve the two-phase Navier–Stokes equations. In their study Peregrine breather dynamics was investigated up to the initial stages of wave breaking.

In Sect. 2, the difference between the spatial and temporal evolution of the wave field is discussed. In Sect. 3, we give details about the solver that is based on the conformal mapping method and stress that the resulting numerical solution describes the temporal evolution starting from an

95 initial spatial distribution. In Sect. 4, the computational results are discussed for both the temporal evolution problem and then for the spatial evolution case. The corresponding experimental results are also presented and compared directly with the numerical simulations. In Sect. 5, the numerical and experimental results are discussed and the conclusions are drawn.

2 Wave parameters: temporal vs. spatial evolution cases

- 100 The CS model enables computation of wave field evolution in time, starting from a given spatial distribution as an initial condition. In laboratory experiments, however, waves are generated by a wavemaker usually placed at one end of the experimental facility. The experimental data are commonly accumulated only at preselected fixed locations within the tank where the sensors are placed. Quantitative comparison of numerical computations with experimental results gained in those experiments
- 105 may thus constitute a complicated task. For a narrow-banded wave field this problem has been considered by Shemer and Dorfman (2008). For such wave fields, the envelope equations like the NLS and Dysthe models often provide adequate results. In the narrow-banded models the temporal t and the spatial x coordinates are related by the group propagation velocity, c_g , thus enabling modification of the governing temporal evolution equations to a spatial form. The spatial form of the Dysthe
- 110 model was presented by Lo and Mei (1985). Numerical computations based on the Dysthe model for unidirectional wave groups propagating in a long wave tank indeed provided good agreement with experiments (Shemer et al., 2002). The spatial version of the Dysthe equation was also derived from the spatial form of the Zakharov equation (Shemer et al., 2001, 2007) that is free of any restrictions on the spectrum width (Kit and Shemer, 2002).
- As demonstrated in Shemer and Dorfman (2008), the availability of the spatial form of the evolution model is insufficient to pose the initial conditions for the numerical simulations that correspond exactly to those in experiments. In the present work, the temporal evolution is computed by a fully nonlinear solver of the two-dimensional potential equations in finite water depth. Following earlier works (Shemer and Alperovich, 2013; Shemer and Liberzon, 2014), the solution of the spatial
- 120 version of the NLS equation is used to set the initial conditions. For a narrow-banded deep-water wave group, the spatial and temporal variations of the surface elevation z at the leading order can be presented as

$$\zeta(x,t) = Re\left[a(x,t) \cdot e^{i(k_0 x - \omega_0 t)}\right] \tag{1}$$

Here the radian frequency $\omega_0 = 2\pi/T_0$, T_0 being the carrier wave period, and the wave number 125 $k_0 = 2\pi/\lambda_0$, λ_0 being the carrier wave length, satisfy the finite water depth dispersion relation $\omega_0^2 = gk_0 \tanh(k_0h)$. In Eq. (1), a is the slowly varying complex group envelope. The wave steepness is defined as $\epsilon = a_0k_0$, where a_0 is the characteristic wave amplitude. The wave train given by Eq. (1) propagates with the group velocity $c_g = \left(\frac{\partial \omega}{\partial k}\right)_{k=k_0}$. Following Mei (1989) and Shemer et al. (1998), in intermediate water depth the spatial NLS equation for the complex normalized envelope, $Q = a(x,t)/a_0$ is given by:

$$-iQ_X + \alpha Q_{TT} + \beta |Q|^2 Q = 0 \tag{2}$$

where the scaled dimensionless temporal and spatial coordinates are $T = \epsilon \omega_0 (x/c_g - t)$ and X = $\epsilon^2 k_0 x$ respectively. The coefficients in the NLS equation have the following dimensionless form

$$\alpha = -\frac{\omega_0^2}{2k_0 c_g^3} \frac{\partial c_g}{\partial k}$$

$$135 \quad \beta = \frac{1}{n} \left[\frac{\cosh(4k_0h) + 8 - 2\tanh^2(k_0h)}{16\sinh^4(k_0h)} - \frac{1}{2\sinh^2(2k_0h)} \frac{(2\cosh^2(k_0h) + n^2)}{\frac{k_0h}{\tanh(k_0h)} - n^2} \right] \frac{1}{n} \left[\frac{\cosh(4k_0h) + 8 - 2\tanh^2(k_0h)}{16\sinh^4(k_0h)} - \frac{1}{2\sinh^2(2k_0h)} \frac{(2\cosh^2(k_0h) + n^2)}{\frac{k_0h}{\tanh(k_0h)} - n^2} \right] \frac{1}{n} \left[\frac{\cosh(4k_0h) + 8 - 2\tanh^2(k_0h)}{16\sinh^4(k_0h)} - \frac{1}{2\sinh^2(2k_0h)} \frac{(2\cosh^2(k_0h) + n^2)}{\frac{k_0h}{\tanh(k_0h)} - n^2} \right] \frac{1}{n} \left[\frac{\cosh(4k_0h) + 8 - 2\tanh^2(k_0h)}{16\sinh^4(k_0h)} - \frac{1}{2\sinh^2(2k_0h)} \frac{(2\cosh^2(k_0h) + n^2)}{\frac{k_0h}{\tanh(k_0h)} - n^2} \right] \frac{1}{n} \left[\frac{\cosh(4k_0h) + 8 - 2\tanh^2(k_0h)}{16\sinh^4(k_0h)} - \frac{1}{2\sinh^2(2k_0h)} \frac{(2\cosh^2(k_0h) + n^2)}{\frac{k_0h}{\tanh(k_0h)} - n^2} \right] \frac{1}{n} \left[\frac{\cosh(4k_0h) + 8 - 2\tanh^2(k_0h)}{16\sinh^4(k_0h)} - \frac{1}{2\sinh^2(2k_0h)} \frac{(2\cosh^2(k_0h) + n^2)}{\frac{k_0h}{\tanh(k_0h)} - n^2} \right] \frac{1}{n} \left[\frac{\cosh(4k_0h) + 8 - 2\tanh^2(k_0h)}{16\sinh^4(k_0h)} - \frac{1}{2\sinh^2(2k_0h)} \frac{(2\cosh^2(k_0h) + n^2)}{16\sinh^4(k_0h)} - \frac{1}{2\sinh^2(k_0h)} \frac{(2\cosh^2(k_0h) + n^2)}{16\sinh^4(k_0h)} - \frac{1}{2\sinh^2(k_0h)} \frac{(2\cosh^2(k_0h) + n^2)}{16\hbar^2(k_0h)} - \frac{1}{2\hbar^2(k_0h)} - \frac{1}{2\hbar^2(k_0h)} \frac{(2\cosh^2(k_0h) + n^2)}{16\hbar^2(k_0h)} - \frac{1}{2\hbar^2(k_0h)} \frac{(2\hbar^2(k_0h) + n^2)}{16\hbar^2(k_0h)} - \frac{1}{2\hbar^2(k_0h)} \frac{(2\hbar^2(k_0h) + n^2)}{16\hbar^2(k_0h)} - \frac{1}{2\hbar^2(k_0h)} - \frac{1}{2\hbar^2(k_0h)} \frac{(2\hbar^2(k_0h) + n^2)}{16\hbar^2(k_0h)} - \frac{1}{2\hbar^2(k_0h)} -$$

145

(4)

 $\overline{2\sinh^2(2k)}$

where the parameter $n = c_{\rm g}/c_{\rm p}$ represents the ratio of group and phase velocities and is given by

$$n = \frac{1}{2} \left\{ 1 + \frac{2k_0 h}{\sinh(2k_0 h)} \right\}.$$
(5)

For the deep water case, $k_0 h \rightarrow \infty$ and $\alpha = \beta = 1$. The Peregrine Breather solution of the NLS equation for intermediate water depth (Eq. 2) is:

140
$$Q = -\sqrt{2\frac{\alpha}{\beta}}e^{-2i\alpha X} \left[1 - \frac{4(1 - 4i\alpha X)}{1 + 4T^2 + 16(\alpha X)^2} \right]$$
(6)

Equations (1) and (6) provide variation of the instantaneous surface elevation in time and in space, with focusing corresponding to T = X = 0. In Shemer and Alperovich (2013) and Shemer and Liberzon (2014), the wavemaker driving signal as a function of time was selected using the deep-water version of Eq. (12) and the prescribed focusing distance from the wavemaker, x_0 , by substituting $X = X_0 = -\epsilon^2 k_0 x_0$ into Eq. (6). The relative height of the initial hump in the wave amplitude distribution at the wavemaker in Shemer and Liberzon (2014) was about exceeded 10 % above the

The present study has been carried out in the 18 m long, 1.2 m wide and 0.9 m deep wave tank (water depth h = 0.6 m). More details about the experimental facility are given in Shemer et al.

- (1998). The carrier wave period $T_0 = 0.8 \,\mathrm{s}$ was selected, corresponding to the carrier wave length 150 $\lambda_0 = 1.0 \text{ m}$ and the dimensionless water depth $k_0 h = 3.77$. For these parameters, both coefficients in the NLS equation (eq0b) given by Eqs. (3) and (4) in fact differ from unity: $\alpha = 1.078$ and $\beta = 0.711$. The carrier wave amplitude of $\zeta_0 = \sqrt{\frac{2\alpha}{\beta}}a_0 = 0.026 \text{ m}$ was used, corresponding to the nonlinearity $\epsilon = k_0 a_0 = 0.094.$
- Given that Since the nonlinear numerical solver in the present study requires an initial condition as 155 a given spatial distribution at a certain instant, the following procedure to determine the appropriate initial spatial distribution was adopted.

background.

be located. Note that in physical terms, this initial condition corresponds to a situation in which the whole wave train is placed upstream of the wavemaker. Due to the focusing properties of the NLS 160 equation in sufficiently deep water ($k_0 h > 1.36$), the maximum wave height in the train increases in the course of the evolution process. In order to obtain the amplification, at the wavemaker location, of about 20% similar to that employed in Shemer and Liberzon (2014), the initial height of the PB

Using Eq. (6), a value of x_0 is specified at which the prescribed maximum crest of the PB is to

hump has to be significantly smaller than that. The amplification corresponding to 5% was selected.

- 165 The temporal variation of the surface elevation at $x = x_0$, $\zeta(x_0, t)$, can be calculated using $T(x_0, t)$ and $X(x_0)$. The maximum amplification occurs at T = 0 corresponding to the dimensional time $t_{\rm max} = -x_0/c_{\rm g}$; the resulting $\zeta(t)$ is symmetric with respect to $t_{\rm max}$. Note that at the instant $t = t_{\rm max}$, the spatial distribution $\zeta(x, t_{\text{max}})$ is not fully symmetric with respect to x_0 due to the presence of term $e^{-2i\alpha X}$ in Eq. (6). It should be stressed that in experiments as well as in numerical simulations, the
- actual extent of the wave group is necessarily finite. In the experiments of Shemer and Alperovich 170 (2013) and Shemer and Liberzon (2014) the wave train with duration of 70 carrier wave periods was generated by the wavemaker. The duration of the wave train of $70T_0$ is long enough to eliminate the effect of truncation to the central part of the train where the hump is located and which is of particular interest, and on the other hand to eliminate sufficiently short to prevent contamination of
- the measured surface elevation by possible reflection from the far end of the tankwaves. In the spatial 175 domain, this duration of the wave train corresponds to $35\lambda_0$. The numerical method applied in the present study assumes spatially periodic boundary conditions. Since the initial spatial distribution is not periodic, the periodicity was enforced by applying a linear tapering window over 2 wave length λ_0 at the edges of the wave train. As a result, the effective, undisturbed by tapering, wave group
- extended initially for about $32\lambda_0$. To allow evolution of the wave train unaffected by boundaries, the 180 computational domain was selected as $[-32\lambda_0, 32\lambda_0]$, with x = 0 corresponding to the location of the maximum crest at the initial instant of the computations, t = 0. The temporal initial condition adopted in the study is plotted in the top panel of Fig. 1. The corresponding spatial variation of the surface elevation with the same maximum crest height is plotted in the bottom panel of the same figure.
- 185

3 Numerical solution methodology

The temporal evolution of the initial wave field presented in the bottom panel of Fig. 1 is obtained by solving potential flow equations following the fully nonlinear numerical approach developed by Chalikov and Sheinin (1998, 2005). The CS model is known to be stable and does not have limitations in terms of wave steepness. It has been extensively and successfully used for numerical 190 simulations of numerous problems related to evolution of nonlinear waves. The conformal mapping method is applied to solve Laplace's equation for the velocity potential. Surface tension effects are neglected. The principal equations are re-written in a surface-following coordinate system (ξ and ζ) and reduced to two time-evolutionary equations for the surface elevation z and velocity potential

 ϕ^{s} at the surface. The evolutionary equations representing the kinematic and dynamic boundary 195 conditions at the free surface are written in terms of the Fourier coefficients of z and ϕ^s . This enables the reduction of the evolutionary equations into a system of time-dependent ordinary differential equations for 4M + 2 Fourier coefficients of z and ϕ^s , coupled with appropriate initial conditions. Here M refers to the truncation number of the Fourier series.

200 The initial surface elevation is given as a function of the physical variable x. To solve the problem in the mapped space, this initial condition has to be converted into a function of equally spaced ξ . This is done by an iteration procedure.

For time integration, a fourth order Runge–Kutta scheme was used. We refer the reader to Chalikov and Sheinin (2005) for further details. In the present computations, the dimensional spatial 205 discretization interval was $\lambda_0/256$, so that the total number of spatial points N = 17,920; the truncation number for the Fourier Series is M = N/9. This value of M effectively means that waves with wavelengths shorter than 1.5 cm where capillary effects become dominant are disregarded. The dimensional integration step in time is $dt = 3.125 \times 10^{-6}$ s. The output-

The CS model allows for the computation of the velocity potential as a function of two parameters: 210 ξ and ζ , the velocity potential for the entire domain can thus be calculated at any instant. In view of the focus of the present study, the output parameters of the numerical integration are the surface elevation z, velocity potential at the surface ϕ^{s} and the physical spatial coordinate x, which are all functions of ξ and t. In order to record the data for future use, the results for surface elevation, the coordinates x and non-dimensional velocity potential are saved at every 3.125 ms. Note also that

spline interpolation procedure is needed to obtain values of the surface elevation z and the velocity potential ϕ^{s} at equally spaced values of x.

Milewski et al. (2010) have also employed the conformal mapping method to investigate the unsteady evolution of two-dimensional fully nonlinear free surface gravity-capillary solitary waves for infinite depth. Though their numerical approach is similar to that of CS, certain differences between

220 the methods exist. The numerical approach of Milewski et al. (2010) was implemented in our computations as well. No significant differences with the results based on the CS model were obtained, thus further demonstrating the robustness of the present results.

4 Numerical and experimental results

- In Fig. 2, the spatial instantaneous wave surface profile is plotted for several characteristic selected instants. As mentioned above, the origin of the frame of references x = 0 corresponds to the location of the maximum crest in the initial spatial distribution. The simulations demonstrate that abnormally high waves appear at both edges of the wave train as a result of truncation and tapering of the infinite wave train defined by Eqs. (1) and (6) as specified in the previous section. Similar phenomenon was observed in experiments with truncated wave trains reported in earlier
- 230 works (Shemer and Alperovich, 2013; Shemer and Liberzon, 2014). The effect of truncation, however, apparently does not extend to the central part of the wave train even at relatively long times, as can be seen from the upper curves in this figure. The effect of nonlinear focusing on the behav-

ior of this central part of the train in the vicinity of the hump is of principal interest in this study. The dashed lines in Fig. 2 originate at the leading edge, the center and the trailing edge of the

- initial wave train and correspond to the location of the point propagating with the group velocity $c_{\rm g} = 0.63 \,\mathrm{m \, s^{-1}}$. It transpires from the figure that the leading edge of the train indeed propagates with the speed that is close to $c_{\rm g}$, while the trailing edge seems to move somewhat faster. The propagation velocity of the steepest crest, however, exceeds notably the group velocity $c_{\rm g}$, in agreement with the experimental observations and the numerical simulation based on the Dysthe equation in
- 240 Shemer and Liberzon (2014) Shemer and Alperovich (2013).

The spatial variation of the velocity of the fluid at the surface $u_{\rm h} = \partial \phi^{\rm s} / \partial x$ is plotted in Fig. 3 at the same instants as in Fig. 2, but in a moving with $c_{\rm g}$ frame of reference. Only the central part of the wave train is shown. The horizontal fluid velocity at the steepest crest increases notably during the focusing process. At the upper curve in Fig. 3, the fast increase in the horizontal velocity at the crest

- results in apparent discontinuity of u_h , thus violating the basic assumptions adopted in the numerical approach and indicating that simulations at larger times may become inaccurate is clearly seen. Note that in earlier experiments by Shemer and Liberzon (2014) wave breaking was indeed observed at comparable distances from the wavemaker.
- The individual waves in Fig. 3 manifest variable left-right asymmetry. Furthermore, it should be stressed that periodic boundary conditions prescribed by the computational model imply that the mean value of the horizontal velocity u_{h} is zero, and the values of the horizontal velocity u_{b} at the boundaries of the computational domain vanish. This actually means that Stokes drift cannot be reproduced in the present numerical simulations. Note that significant Stokes drift was indeed documented in experiments by Shemer and Liberzon (2014).
- 255 Measurements in a wave tank are routinely performed using wave gauges spread along the facility. To facilitate facilitate the direct comparison between numerical and experimental results, we need to first determine the location of the wavemaker in our numerical simulations. Then, we examine vertical cross-sections of the data as presented in Fig. 2 at fixed locations relative to the adopted coordinate of the wavemaker. The location of the wavemaker is identified by the vertical line in the
- 260 latter figure where $x = x_{wm} = 25.273$ m. The temporal variation of the surface elevation is plotted in Fig. 4 at selected locations that cover the range of the wave gauge positions in the experiment, starting with that at x_{wm} or $x_* = 0$, the variable x_* denoting the distance from the wavemaker. The disturbances at the leading edge of the truncated wave group are disregarded here. The growth of the maximum crest height with the distance is obvious, albeit non-monotonic. In the uppermost curve
- in Fig. 4 the relative crest amplification exceeds the factor of 2, as in Shemer and Liberzon (2014) at a comparable distance from the wavemaker. Here again, the broken line that corresponds to the propagation velocity of $c_{\rm g}$ clearly shows that the steepest crests in the train propagate at velocities exceeding $c_{\rm g}$.

A closer look at the surface elevation variation with time is presented in Fig. 5; the time here

- 270 is shifted at each position by delay that would occur if the hump in the group indeed propagated with the group velocity. Actually, the maximum crest is invariably observed earlier. Both the vertical (trough-crest) and the horizontal (right-left) asymmetries of steep waves are clearly visible in the plotted records.
- In Fig. 6, we follow after the highest crests in the instantaneous snapshots of wave trains. The 275 elevations of the highest crests at each instant are compared with the propagation velocity of those crests, v_{cr} . To enable comparison of parameters with different dimensions, crest heights are normalized by the background wave amplitude ζ_0 , while crest propagation velocities are normalized by the <u>carrier wave</u> phase velocity c_p . Note that this figure corresponds to evolution times at which the hump's amplification is still relatively modest. Nevertheless, the crests propagate with time-280 dependent velocities v_{cr} that may be notably different from c_p as would be the case for a purely monochromatic wave train. It was demonstrated in experiments of Shemer and Liberzon (2014) that
- even for waves in the train that are far away from the hump and thus seem to be essentially monochromatic, the mean crest propagation velocity is somewhat higher than c_p due to two main factors: the presence of the exponential term in Eq. (6), and Stokes drift current due to nonlinearity. As stressed
- above, in the present computations the Stokes drift is absent as a result of the prescribed periodicity of the boundary conditions. The instantaneous steep crest velocities in Fig. 6 differ from c_p , as well as from the computed by Shemer and Liberzon (2014) behavior of v_{cr} for the Peregrine breatherby Shemer and Liberzon (2014). It transpires from the comparison of the two curves in Fig. 6 that the higher are the crests, the lower is their propagation velocity. The minima in the instantaneous max-
- imum crests heights correspond to the local maxima in their instantaneous propagation velocities. The averaged highest crest propagation velocity in Fig. 6 is $1.253 \,\mathrm{m\,s^{-1}}$, slightly above c_{p} .

The experiments were carried out with the goal to enable quantitative comparison of the numerical results with experiments. The wavemaker driving signal was designed to generate surface elevation variation in time corresponding to the lowest curve in Fig. 4. Measurements were performed by

- 295 multiple (up to four) resistance-type wave gauges placed on a bar in the center of the tank and connected to a computer-controlled carriage. The spacing between adjacent gauges was 0.4 m. At each run, the position of the carriage was set by computer. Each successive run was initiated only after any disturbance of the water surface from the previous run had fully decayed. Measurements performed in different runs at fixed locations demonstrated excellent repeatability of results. Thus, the
- 300 data collected at different locations obtained in various runs could be compared using the initiation of the wavemaker driving signal as a common temporal reference. Multiple experimental runs with different carriage positions provided experimental records of the temporal variation of the surface elevation in the wave train propagating along the whole tank with spacing that did not exceed 0.2 m; denser measurements were carried out in the vicinity of the locations where inception of breaking
- 305 was detected in visual observations.

An example of the sequence of the experimentally recorded wave trains for $6.6 \le x \le 7.8$ m is presented in Fig. 7. Modifications of the wave train shape between the adjacent locations are relatively minor. The variation along the tank of the location and height of the steepest crest in the central part of the train can be easily followed from these records. Note that the highest crest at x = 7.6 m

310 ceases to be such at x = 7.8 m, where the following wave in the train becomes the steepest one. Such a transition of the highest crest in the train from one wave to another that causes discontinuity in the velocity of propagation of the steepest crest was already noticed in Shemer and Liberzon (2014).

It is impractical to carry out direct comparison of the fast varying surface elevation records measured in the experiments as presented in Fig. 7, with the corresponding numerical results. In or-

315 der to compare directly the computed and the measured results, the corresponding envelopes were computed; the absolute values of the measured and simulated wave train envelopes are presented in Fig. 8 for various distances from the wavemaker. To calculate the envelopes of the wave train in both simulations and in experiments, the records were first band-pass filtered in the domain 0.5ω₀ ≤ ω ≤ 1.5ω₀. This procedure leaves only the "free" waves, while the higher order "bound"
320 waves that cause vertical asymmetry of the records are removed. The envelopes of the filtered signals were then computed using the Hilbert transform. For more details, see e.g. Shemer et al. (1998).

Figure 8 demonstrates that essential similarity exists between the shapes of the measured wave trains at different distances from the wavemaker and those obtained in the numerical simulations. The propagation velocities of the leading edge of the wave train, as well as of the steepest crest, are also
quite close in simulations and in experiments. The agreement between the numerical solution and the experimental results is, however, not perfect; the differences cannot be attributed to experimental errors only.

Important parameters of the wave train in the course of its propagation along the tank obtained in the simulations are plotted in Figs. 9 and 10. In Fig. 9, the temporal variation of the computed ve-

- 330 locities of the highest crests at each instant, v_{cr} , and of the fluid velocity at those crests, u_h^{max} are presented at late stages of the evolution, up the the apparent breakdown of computations at $t/T_0 \approx 74$. However, the maximum crest height amplification exceeding 3 was observed at $t/T_0 \approx 62$. The maximum crest elevations are also plotted in this figure for comparison. To enable comparison, all data are rendered dimensionless by normalizing them by their appropriate characteristic values. The fluid
- 335 velocities increase with crest heights, while the crest propagation velocities decrease. At final stages the fluid velocity at the crest seems to exceed the crest velocity. The corresponding spatial variations are plotted in Fig. 10. In this figure, whenever available, the related experimental results are plotted as well.

The evolution of the steepest crest heights along the tank, as plotted in Fig. 10, in simulations and in experiments exhibit qualitative and to some extent quantitative similarity. The steepest crest heights have a tendency to grow along the tank; this growth is essentially non-monotonic in computations as well as in measurements. At distances from the wavemaker beyond 7 m the measured steepest crest heights may exceed the background by a factor of 2.5; the amplification factor in simulations is somewhat higher than that. The propagation velocity of the steepest crest, v_{cr} , varies to

- 345 a certain extent in experiments and in computations, remaining close to the phase velocity of the carrier wave, $c_{\rm p}$. The discontinuity in the steepest crest propagation velocity obtained in the experiments is related to the transition of the steepest crest in the train from one wave to another, as discussed with relation to Fig. 7. The spatial resolution of the determination of $v_{\rm cr}$ is obviously much better in the numerical simulations than in the experiments. For that reason, oscillations of the measured
- 350 steepest crest velocity are less pronounced in the experimental results. As discussed with respect to the temporal variation of c_{cr} in Fig. 6, the crest propagation velocity decreases when crests become higher. This feature is more visible in the results of simulations as compared to the measurements due to their better resolution.

The bottom curve in Fig. 10 represents the variation along the tank of the instantaneous water
particle velocity at the steepest crest, computed as u^{max}_h = ∂φ^s/∂x at the crest. This velocity varies in accordance with the variation of the crest height; as the crest becomes higher, the values of u^{max}_h grow and may exceed notably the group velocity c_g. Nevertheless, for the whole domain of computations the horizontal liquid velocity at the crest remains lower than the computed v_{cr}. Note that the computed temporal variations of v_{cr} and u^{max}_h plotted in Fig. 9 demonstrate that the values of v_{cr}
may decrease below the local maximum of u^{max}_h, however, this does not occurs simultaneously. No measurements of u^{max}_h were carried out in this study, however, detailed results on the Lagrangian kinematics at the wave crest approaching breaking obtained using Particle Tracking Velocimetry

- (PTV) were presented for the identical carrier wave parameters and somewhat different wavemaker driving signal in Shemer and Liberzon (2014).
- 365 At distances exceeding about 7 m from the wavemaker, the pattern of variation of the steepest crests height and of their propagation velocity v_{cr} plotted in Fig. 10 becomes less organized. In experiments, inception of spilling breaker was observed at those distances, see the video in the Supplement. In order to obtain more accurate estimates of v_{cr} in this region, measurements of the surface elevation were performed each 0.1 m. The resulting steepest crest propagation velocities are plotted in Fig. 10 using different symbols. These results demonstrate that at the locations where the
- spilling breakers were observed, the measured $v_{\rm cr}$ may indeed fall below the computed water surface velocity at the crest, $u_{\rm h}^{\rm max}$.

It was suggested in Shemer and Liberzon (2014) that spilling breaker appear when the the horizontal water particle velocity at the steep crest $u_{\rm h}^{\rm max}$ attains instantaneous crest propagation velocity

375 $v_{\rm cr}$. While spilling breakers were clearly seen in the experiments at distances of about 7.5–8 and 8.5–9 m from the wavemaker, as can be observed in the video in the Supplement, in computations the values of $u_{\rm h}^{\rm max}$, while increasing at steep crests, remain consistently lower by about 10 % than the computed $v_{\rm cr}$, although extremely low steepest crest propagation velocities were occasionally obtained numerically, see Fig. 9. The experimentally determined values of crest propagation velocity may indeed fall below the computed water particle velocity $u_{\rm h}^{\rm max}$.

380

In this respect it should be stressed that the velocities $u_{\rm h}^{\rm max}$ and $v_{\rm cr}$ obtained in the present fully nonlinear numerical simulations, while apparently being close to their actual values as demonstrated in Fig. 10, cannot be seen as the exact ones. One obvious reason for that inaccuracy is the lack of the Stokes drift in the computational results due to the imposed periodicity of the boundary conditions.

- 385 The Stokes drift is an experimental reality and constitutes about 3 % of c_p ; accounting for the Stokes drift velocity can thus immediately shrink the gap between u_h^{max} and v_{cr} at the steepest crests in the numerical simulations. The experimental determination of v_{cr} as performed in the present study is inaccurate mainly due to the presence of unavoidable low-level noise in the surface elevation records that limit the precision of defining the instant when the maximum surface elevation is attained. The
- 390 PTV-derived results on $u_{\rm h}^{\rm max}$ presented in Fig. 7 of Shemer and Liberzon (2014) show that horizontal surface velocities as high as $0.8c_{\rm p}$, notably higher than the maximum values of $u_{\rm h}^{\rm max}$ in Fig. 10, were indeed measured at the breaking location. It thus can be concluded that the differences between $u_{\rm h}^{\rm max}$ and $v_{\rm cr}$ obtained numerically as presented in 10 stem from less than perfect accuracy of the model. The total body of numerical and experimental results thus confirms the provides further support to
- 395 the validity of the kinematic breaking criterion according to which the spilling breaker emerges when the instantaneous liquid velocity at the crest, $u_{\rm h}^{\rm max}$, attains that of the crest, $v_{\rm cr}$.

The amplitude spectra of the wave train are plotted in Figs. 11 and 12. In Fig. 11 the numericallyderived frequency spectra of $\eta(t)$ are compared at selected values of x_* with the corresponding experimental results. At the wave maker ($x_* = 0$), the spectrum in linear-logarithmic coordinates still

- 400 retains resemblance to triangular shape characteristic for Peregrine Breather. Nevertheless, a weak asymmetry around the dominant frequency ω_0 can already be noticed at this location. Note that at $x_* = 0$ the wave train already evolved over significant duration from its initial PB shape in Fig. 1. The non-negligible contribution of low frequency as well as 2nd and 3rd bound wave harmonics is also evident. The spectral asymmetry gets stronger and the spectrum widens with the distance from the
- 405 wave maker. Reasonable agreement is obtained between the experimental and the numerical results. The wavenumber spectrum for the computed variation of $\eta(x)$ plotted in Fig. 12 at selected instants t cannot be compared with experiment. This is due to the fact that the spatial extent of the wave train exceeds significantly the length of the tank, see Fig. 2. Note that even for significantly shorter wave trains, the experimental procedure that enables extracting wavenumber spectra (as opposed to
- 410 frequency spectra) is extremely tedious, see Shemer and Dorfman (2008). The temporal evolution of wavenumber spectra in Fig. 12 is qualitatively similar to that discussed with respect to Fig. 11. An initial nearly symmetric around the dominant wavenumber spectrum becomes more asymmetric and the spectrum widens as time increases towards breaking.

5 Discussion and conclusions

- 415 In the present study, fully nonlinear numerical simulations of evolution of a unidirectional nonlinear wave train with an initial shape of a Peregrine Breather were qualitatively and quantitatively compared with the experimental results. The simulations were carried out using a conformal mapping approach as detailed in Chalikov and Sheinin (2005). To validate the accuracy of the code, the computational results were reproduced using an alternative numerical approach of Milewski et al.
- 420 (2010). These and some other numerical methods that are often applied to solve wave propagation problems require complete information on the wave field over the entire computational range at a certain instant. These initial conditions are unavailable in any controlled wave experiment in a laboratory facility. The unidirectional wave field in a tank is in fact prescribed by the wavemaker that is usually located at one end of the facility and driven by a computer generated signal.
- The initial condition in experiments thus corresponds to surface elevation variation with time at a prescribed wavemaker location. To reconcile between the initial spatial distribution of wave field parameters required for the numerical solution, and the temporal variation of the surface elevation at the wavemaker prescribed as the initial condition in the experiments, the approach originally applied in Shemer and Dorfman (2008) was generalized here to a fully nonlinear wave field with an arbitrary
- 430 spectral width. This generalization makes it possible to carry out consistent quantitative comparison of the results of numerical simulations and of measurements.

In the present simulations, the initial spatial distribution of the surface elevation is based on the PB analytical solution. In order to determine in the numerical solution the measurable temporal variation of the surface elevation at any given location along the tank, the initial spatial distribution

- 435 in the present study was centered upstream of the wavemaker, see Fig. 2. The appropriate location of the wavemaker was determined then by comparing the surface elevation variation in time with that measured in the experiment. The wavemaker driving signal generates surface elevation variation in time that corresponds to the bottom curve in Fig. 4. This dependence that is very different from the analytical solution given by PB is obtained as a result of evolution of the wave train with an initial
- 440 shape given in the bottom panel of Fig. 1. It enables detailed and quantitative comparison of the simulations with experiment.

Several important points regarding PB were highlighted in this study. The solution (6) of the spatial form of the nonlinear Schrödinger equation (2) is asymmetric aperiodic in space due to the presence of an exponential term. Similarly, the temporal form of the NLS equation (Lo and Mei,

- 1985; Shemer and Dorfman, 2008) yields PB that has an asymmetry in time. Moreover, the solution (6) extends to infinity in both time and space whereas in both experiments and experiments as well as in numerical simulations the extent of the wave train is finite in both x and t. The exact shape of the analytical solution (6) thus can be reproduced neither in the experiments nor in numerical simulations
 computations. Note that in the present study, the actual initial condition for the simulations and
- 450 the wavemaker driving signal have been modified and are fundamentally different from PB. The

presented results on steep crests in the wave train are therefore of generic nature and applicable beyond the 2D PB wave packets.

Two different approaches were suggested to deal with those problems the problems outlined in the previous paragraph. In numerical simulations, the truncated wave train with the spatial exten-

- 455 sion that contains an integer number of carrier wave lengths is often used as the initial condition (Slunyaev and Shrira, 2013). However, imposing a non-zero periodic boundary condition on an essentially aperiodic function may affect significantly the nature of the solution. It was thus decided in the present study to follow the experimental approach of Shemer and Alperovich (2013) and Shemer and Liberzon (2014). The theoretical solution given by Eq. (6) was truncated and tapered
- 460 before being used to determine the initial condition at the wavemaker. In order to mitigate the effect of truncation on the central part of the wave train, a sufficiently large number of wave periods (about 70) was used in those experiments. A similar approach was adopted in the present study. As can be seen in both experimental and numerical results (Figs. 1, 4 and 9), truncation and tapering, while indeed satisfying periodic boundary conditions in the computational domain, cause appearance of
- 465 abnormally high waves at the leading and trailing edges of the wave train. The effect of truncation is apparently limited to the edges of the train, and does not affect the behavior of the central part of PB-PB-like wave train with the gradually amplified, albeit non-monotonically, hump in the envelope. These high waves do not characterize the Peregrine-wave train proper and therefore were disregarded in the present study.
- 470 The computational results indeed are in a good qualitative and to a <u>certain large</u> extent quantitative agreement with the current experiments, as well as with those of Shemer and Liberzon (2014). This includes the behavior of the truncated train edges, the amplification of the hump along the tank, the asymmetric spectral widening, as well as the variation of the envelope shape along the tank. Of particular interest is the slowdown of steep crests in PB wave train that Crest slowdown was
- 475 noted by Johannssen and Swan in fully-nonlinear calculations (Johannessen and Swan, 2001) and experiments (Johannessen and Swan, 2003). The slowdown of crests in PB-like wave train as they grow in height was first observed by Shemer and Liberzon (2014). In somewhat different contextin experiments and NLS solutions and is of particular interest More recently, this effect was also stressed recently in Banner et al. (2014) and in Kurnia and Groesen (2014) in the context of focusing
- 480 of 2D and 3D nonlinear deep water wave packets by Banner et al. (2014), for 2D nonlinear wave packets byKurnia and Groesen (2014) as well as by Fedele (2014), thus providing additional evidence to the generic nature of the phenomenon. It was noticed in Shemer and Liberzon (2014) that the increase in the maximum crest height along the tank is not monotonic. As the maximum crest height increases, the water particles at the crest accelerate to higher maximum velocities u_h^{max} , while
- 485 the crest propagation speed v_{cr} decreases. The equality $u_{h}^{max} = v_{cr}$ was thus suggested as the kinematic criterion for wave breaking. A slightly different version of this criterion was offered by Kurnia and Groesen (2014); they maintain that the maximum liquid particle velocity u_{h}^{max} exceeds

about $0.8v_{cr}$ at breaking. If only the simulations are considered, it seems that this somewhat weaker version of the kinematic breaking criterion is confirmed. However, the present experimental results

- 490 indicate as well as numerical results, combined with those obtained experimentally by alternative methods in Shemer and Liberzon (2014), provide a strong, albeit not fully conclusive, support to the conjecture that indeed the particle velocities at breaking the inception of breaking attain and exceed the crest propagation velocities , thus confirming and thus to the kinematic breaking criterion in the formulation suggested by Shemer and Liberzon (2014) in that study. This conjecture is further
- 495 corroborated by visual evidence as seen in video clips presented in Supplements to Shemer and Liberzon (2014) and to the present study.

This combined numerical and experimental study of nonlinear wave trains also clarifies the limitations of the adopted fully nonlinear solution method. The procedure of truncation and tapering of the initial condition applied here does not solve all the problems associated with imposing the

- 500 periodic boundary conditions in the numerical solution. The prescribed spatial periodicity of the velocity potential effectively eliminates appearance of the 2nd order Stokes drift current, thus resulting in an inaccurate horizontal velocity at the liquid surface. As demonstrated by Shemer and Liberzon (2014), the Stokes drift is actually observed in laboratory experiments. In this respect it should be stressed that, while the periodicity in the time domain is possible for propagating unidirectional
- 505 waves, they are, strictly speaking, aperiodic in space. This point adds an additional aspect to essential differences that exist between the spatial and temporal formulations of the wave evolution problem, as discussed above. All nonlinear solutions that are based on spatially periodic boundary conditions, as in the method adopted here, as well as in a variety of alternative methods that employ spatial discrete Fourier decomposition, therefore contain intrinsic inaccuracy already at the 2nd or-
- 510 der in the nonlinearity parameter ϵ . These numerical solutions thus can only provide approximate results and require careful experiments to verify their validity. The present study shows that the fully nonlinear solution, although flawed, yields better agreement with experiments than the application of the limited to the 3rd order spatial version of the modified nonlinear Schrödinger (Dysthe) equation that does not require spatial periodicity (Shemer and Alperovich (2013).
- 515 The support of this study by a grant 20102019 from the U.S.-Israel Binational Science Foundation is gratefully acknowledged. The authors wish to thank Mr. Andrey Zavadsky for his valuable assistance.

References

520

Akhmediev, N. N., Eleonskii, V. M., and Kulagin, N. E.: Exact first-order solutions of the nonlinear Schrödinger equation, Theor. Math. Phys., 72, 809–818, 1987.

Babanin, A., Chalikov, D., Young, I., and Savelyev, I.: Predicting the breaking onset of surface water waves, Geophys. Res. Lett., 34, L07605, doi:10.1029/2006GL029135, 2007.

Banner, M. L., Barthelemy, X., Fedele, F., Allis, M., Benetazzo, A., Dias, F., and Peirson, W. L.: Linking reduced breaking crest speeds to unsteady nonlinear water wave group behavior, Phys. Rev. Lett., 112, 114502,

525 doi:10.1103/PhysRevLett.112.114502, 2014.

Bateman, W. J. D., Kasardi, V., and Swan, C.: Extreme ocean waves. Part I. The practical application of fully nonlinear wave modeling, Appl. Ocean. Res., 34, 209–224, 2012.

- Chalikov, D. and Sheinin, D.: Direct modeling of one-dimensional nonlinear potential waves, Nonlinear Ocean Waves, W. Perrie, Ed., Adv. Fluid Mech. Ser., 17, 207–258, 1998.
- 530 Chalikov, D. and Sheinin, D.: Modeling of extreme waves based on equations of potential flow with a free surface, J. Comput. Phys., 210, 247–273, 2005.

Dysthe, K. B.: Note on the modification of the nonlinear Schrödinger equation for application to deep water waves, P. Roy. Soc. Lon. A Mat., 369, 105–114, 1979.

- Dysthe, K. B. and Trulsen, K.: Note on breather type solutions of the NLS as models for freak-waves, Phys.
 Scripta, 82, 48, doi:10.1238/Physica.Topical.082a00048, 1999.
- Dysthe, K., Krogstad, H. E., and Müller, P.: Oceanic rogue waves, Annu. Rev. Fluid Mech., 40, 287–310, 2008. Fedele, F.: Geometric phases of water waves, EPL, 107(6),69001, http://dx.doi.org/10.1209/0295-5075/107/69001, 2014.

Hasimoto, H. and Ono, H.: Nonlinear modulation of gravity waves, J. Phys.Soc. Jpn., 33, 805-811, 1972.

- Johannessen, T. B., and Swan, C.: A laboratory study of the focusing of transient and directionally spread surface water waves, Proc. R. Soc. A, 457, 971–1006, 2001.
 Johannessen, T. P., and Swan, C.: On the popliator dynamics of wave groups produced by the focusing of
 - Johannessen, T. B., and Swan, C.: : On the nonlinear dynamics of wave groups produced by the focusing of surface water waves, Proc. R. Soc. A, 459, 1021–1052, 2003.
 - Kharif, C., Pelinovsky, E., and Slunyaev, A.: Rogue Waves in the Ocean, Springer Verlag, Germany, 2009.
- 545 Kit, E. and Shemer, L.: Spatial versions of the Zakharov and Dysthe evolution equations for deep water gravity waves, J. Fluid Mech., 450, 201–205, 2002.
 - Kurnia, R. and Groesen, E. V.: High order Hamiltonian water wave models with wave-breaking mechanism, Coast. Eng., 93, 55–70, 2014.

- 550 Lo, E. and Mei, C. C.: A numerical study of water-wave modulation based on higher-order nonlinear Schrödinger equation, J. Fluid Mech., 150, 395–416, 1985.
 - Ma, Y. C.: The perturbed plane-wave solutions of the cubic Schrödinger equation, Stud. Appl. Math., 60, 43–58, 1979.

Mei, C. C.: The Applied Dynamics of Ocean Surface Waves, World Scientific, Singapore, 1989.

555 Milewski, P. A., Vanden-Broeck, J. M., and Wang, Z.: Dynamics of steep two-dimensional gravity-capillary solitary waves, J. Fluid Mech., 664, 466–477, 2010.

Kuznetsov, E. A.: Solitons in a parametrically unstable plasma, Akad. Nauk SSSR Dokl., 236, 575–577, 1977.

- Osborne, A., Onorato, M., and Serio, M.: The nonlinear dynamics of rogue waves and holes in deep-water gravity wave train, Phys. Lett. A, 275, 386–393, 2000.
- Peregrine, D. H.: Water waves, nonlinear Schrödinger equations and their solutions, J. Aust. Math. Soc. B, 25, 16–43, 1983.

560

- Perić, R., Hoffmann, N., and Chabchoub, A.: Initial wave breaking dynamics of Peregrine-type rogue waves: a numerical and experimental study, Eur. J. Mech. B-Fluids, 49, 71–76, 2014.
- Phillips, O. M.: The equilibrium range in the spectrum of wind generated waves, J. Fluid Mech., 4, 426–434, 1958.
- 565 Shemer, L.: On kinematics of very steep waves, Nat. Hazards Earth Syst. Sci., 13, 2101–2107, doi:10.5194/nhess-13-2101-2013, 2013.
 - Shemer, L. and Alperovich, L.: Peregrine Breather revisited, Phys. Fluids, 25, 051701, doi:10.1063/1.4807055, 2013.
- Shemer, L. and Dorfman, B.: Experimental and numerical study of spatial and temporal evolution of nonlinear
 wave groups, Nonlin. Processes Geophys., 15, 931–942, doi:10.5194/npg-15-931-2008, 2008.
- Shemer, L. and Liberzon, D.: Lagrangian kinematics of steep waves up to the inception of a spilling breaker, Phys. Fluids, 26, 016601, doi:10.1063/1.4860235, 2014.

Shemer, L., Kit, E., Jiao, H., and Eitan, O.: Experiments on nonlinear wave groups in intermediate water depth, J. Waterw. Port C.-ASCE, 124, 320–327, 1998.

- 575 Shemer, L., Jiao, H. Y., Kit, E., and Agnon, Y.: Evolution of a nonlinear wave field along a tank: experiments and numerical simulations based on the spatial Zakharov equation, J. Fluid Mech., 427, 107–129, 2001.
 - Shemer, L., Kit, E., and Jiao, H. Y.: An experimental and numerical study of the spatial evolution of unidirectional nonlinear water-wave groups, Phys. Fluids, 14, 3380–3390, 2002.
- Shemer, L., Goulitski, K., and Kit, E.: Evolution of wide-spectrum wave groups in a tank: an experimental and
 numerical study, Eur. J. Mech. B-Fluid., 26, 193–219, 2007.
 - Shrira, V. I. and Geogjaev, V. V.: What makes the Peregrine soliton so special as a prototype of freak waves?, J. Eng. Math., 67, 11–22, 2010.

Slunyaev, A., Clauss, G. F., Klein, M., and Onorato, M.: Simulations and experiments of short intense envelope solitons of surface water waves, Phys. Fluids, 25, 067105; doi: 10.1063/1.4811493, 2013.

- 585 Slunyaev, A. V. and Shrira, V. I.: On the highest non-breaking wave in a group: fully nonlinear water wave breathers versus weakly nonlinear theory, J. Fluid Mech., 735, 203–248, 2013.
 - Zakharov, V. E.: Stability of periodic waves of finite amplitude on a surface of deep fluid, J. Appl. Mech. Tech. Phys., 9, 190–194, 1968.



Figure 1. The prescribed initial variation of the surface elevation η in the temporal (top) and spatial (bottom) domains for the carrier wave period $T_0 = 0.8$ s and background carrier amplitude $\zeta_0 = 0.026$ m; calculated for X = -2.613 ($x_0 = 31$ m.) in Eq. (6).



Figure 2. The temporal evolution of the surface elevation η in a fixed reference frame; wave parameters as in Fig. 1. Vertical line marks the location of the wavemaker at $x = x_{wm} = 25.273 \text{ m}$, broken lines correspond to propagation with the group velocity c_{g} .



Figure 3. The temporal evolution of the horizontal fluid velocity in a moving reference frame; wave parameters as in Fig. 1.



Figure 4. Surface elevation variation at fixed values of x_* vs. time t. The group velocity is $c_g = 0.63 \text{ m s}^{-1}$, x_* refers to the wave gauge distance from wavemaker at $x_* = 0$.



Figure 5. The computed temporal variation of the surface elevation at various locations relative to the wavemaker in a moving with c_g reference frame.



Figure 6. The computed variation with time of the normalized maximum crest elevation relative to the background wave amplitude ζ_0 and the velocity of the highest crest propagation (v_{cr}) relative to the phase velocity $c_p = 1.248 \text{ m s}^{-1}$.



Figure 7. Measured surface elevation η at various locations.



Figure 8. Comparison between the envelopes of the measured and numerical surface elevations η at various locations.



Figure 9. The computed temporal variation of the maximum crest heights, of the velocities of the steepest crests (v_{cr}) and of maximum horizontal fluid velocity (u_h^{max}) .



Figure 10. Variation along the tank of the maximum crest heights, propagation velocity of the highest crests and the water particle velocity at those crests. Red lines denote numerical results; blue symbols-experiments. The locations where breaking was observed in the experiments are marked.



Figure 11. Frequency spectra at selected locations. Red line – numerical simulations and blue line – experimental data.



Figure 12. Wavenumber spectra at selected times.